



DIMENSIONS	PROPSHAFT ANGLE		
	10°	12°	15°
A STANDARD	584	612	639
A3 (3" RISER)	596	619	651
A6 (6" RISER)	642	656	676
B	324	329	336
C	627	626	624
D	157	152	143
G	88	94	101
H	251	247	241
J	601	630	672
K	873	858	833
L	74	96	129
N	115	122	131
P	245	232	213
R	208	210	213

METRIC  
MM.

DIMENSIONS	PROPSHAFT ANGLE		
	10°	12°	15°
A STANDARD	23-3/8	24-1/8	25-1/8
A3 (3" RISER)	23-7/16	24-3/8	24-5/8
A6 (6" RISER)	25-1/4	25-13/16	26-5/8
B	12-3/4	12-15/16	13-3/16
C	24-11/16	24-11/16	24-9/16
D	6-3/16	5-15/16	5-5/8
G	3-1/2	3-11/16	4
H	9-7/8	9-3/4	9-1/2
J	23-11/16	24-13/16	26-7/16
K	34-3/8	33-3/4	32-13/16
L	2-15/16	3-13/16	5-1/16
N	4-9/16	4-13/16	5-1/8
P	9-5/8	9-1/8	8-3/8
R	8-3/16	8-1/4	8-3/8

ENGLISH  
IN.

UNIT OF MEASURE  
in. (mm)

SCALE APPROX.  
1" = 1'  
25.4mm = 304mm

MIE 6.2L MPI WITH VELVET DRIVE 72C  
IN-LINE TRANSMISSION.

- (1) DIMENSIONS REQUIRE A MINIMUM 1/2 in. (13mm) CLEARANCE FOR MOTOR MOUNT DEFLECTION.
- (2) BASE OF MOUNT TO BE PARALLEL TO STRINGER. MOUNTS SHOWN AT CENTER OF ADJUSTMENT.
- (3) MINIMUM ANGLE OF EXHAUST DROP 6° (1-1/4 in./ft.) WITH BOAT IN WATER AT REST.
- (4) DIMENSIONS APPLY TO POINT OF INTERSECTION OF OUTPUT SHAFT CENTERLINE AND OUTPUT FLANGE FACE.