



UNIT OF MEASURE in. (mm)	SCALE APPROX. 1" = 1" 25.4mm = 304mm
-----------------------------	--

MIE 8.1L MPI WITH HURTH 630A
DOWN ANGLE TRANSMISSION.

- (1) DIMENSIONS REQUIRE A MINIMUM 1/2 in. (13mm) CLEARANCE FOR MOTOR MOUNT DEFLECTION.
- (2) BASE OF MOUNT TO BE PARALLEL TO STRINGER. MOUNTS SHOWN AT CENTER OF ADJUSTMENT.
- (3) MINIMUM ANGLE OF EXHAUST DROP 6 ° (1-1/4 in./ft.) WITH BOAT IN WATER AT REST.
- (4) DIMENSIONS APPLY TO POINT OF INTERSECTION OF OUTPUT SHAFT CENTERLINE AND OUTPUT FLANGE FACE.

DIMENSIONS	PROPSHAFT ANGLE		
	10°	12°	15°
A3 (3" RISER)	24-15/16	25-5/8	26-9/16
A6 (6" RISER)	27-15/16	28-5/8	29-1/2
B	14-7/8	15-1/16	15-5/16
C	24-1/2	24-1/2	24-3/8
D	5-3/4	5-1/2	5-1/8
E	2-9/16	2-13/16	3-1/4
F	7-1/2	7-1/2	7-9/16
G	4-7/16	4-5/8	4-7/8
H	18	18-7/16	19-1/8
J	18-11/16	19-7/8	21-3/4
K	25-1/16	26-1/4	28
L	3-1/4	4-1/16	5-3/8
M	5-5/8	5-3/8	4-15/16
N	13-7/8	13-3/8	12-1/2
P	7-9/16	7-1/8	6-3/8
R	11-1/2	11-5/8	11-3/4
S	13-3/4	13-15/16	14-3/16
T	4-3/4	4-7/16	3-7/8
U	3-3/4	3-7/8	4-1/8

ENGLISH
IN.

DIMENSIONS	PROPSHAFT ANGLE		
	10°	12°	15°
A3 (3" RISER)	634	651	674
A6 (6" RISER)	710	727	780
B	378	383	389
C	622	622	619
D	147	140	130
E	65	72	83
F	190	190	193
G	112	117	124
H	457	469	486
J	474	505	552
K	637	667	712
L	82	104	136
M	143	136	126
N	353	339	318
P	192	180	162
R	292	295	299
S	349	354	360
T	121	112	98
U	95	99	105

METRIC
MM.