



DIMENSIONS	PROPSHAFT ANGLE		
	10°	12°	15°
A STANDARD	601	630	672
A3 (3" RISER)	601	630	672
A6 (6" RISER)	642	656	676
B	315	318	322
C	636	637	638
D	157	152	143
G	88	94	101
H	251	247	241
K	873	858	833
L	57	35	2
N	115	122	131
P	245	232	213
R	208	210	213

METRIC
MM.

DIMENSIONS	PROPSHAFT ANGLE		
	10°	12°	15°
A STANDARD	23-11/16	24-13/16	26-7/16
A3 (3" RISER)	23-11/16	24-13/16	26-7/16
A6 (6" RISER)	25-1/4	25-13/16	26-5/8
B	12-7/16	12-9/16	12-11/16
C	25-1/16	25-1/16	25-1/8
D	6-3/16	5-15/16	5-5/8
G	3-1/2	3-11/16	4
H	9-7/8	9-3/4	9-1/2
K	34-3/8	33-3/4	32-13/16
L	2-1/4	1-3/8	1/16
N	4-9/16	4-13/16	5-1/8
P	9-5/8	9-1/8	8-3/8
R	8-3/16	8-1/4	8-3/8

ENGLISH
IN.

UNIT OF MEASURE in. (mm)	SCALE APROX. 1" = 1' 25.4mm = 304mm
-----------------------------	---

MIE 5.7L WITH VELVET DRIVE
72C IN-LINE TRANSMISSION.

- (1) DIMENSIONS REQUIRE A MINIMUM 1/2 in. (13mm) CLEARANCE FOR MOTOR MOUNT DEFLECTION.
- (2) BASE OF MOUNT TO BE PARALLEL TO STRINGER. MOUNTS SHOWN AT CENTER OF ADJUSTMENT.
- (3) MINIMUM ANGLE OF EXHAUST DROP 6 ° (1-1/4 in./ft.) WITH BOAT IN WATER AT REST.
- (4) DIMENSIONS APPLY TO POINT OF INTERSECTION OF OUTPUT SHAFT CENTERLINE AND OUTPUT FLANGE FACE.