



UNIT OF MEASURE in. (mm)	SCALE APPROX. 1" = 1" 25.4mm = 304mm
-----------------------------	--

MIE 6.2L MPI WITH VELVET DRIVE 5000V
V-DRIVE TRANSMISSION.

- (1) DIMENSIONS REQUIRE A MINIMUM 1/2 in. (13mm) CLEARANCE FOR MOTOR MOUNT DEFLECTION.
- (2) BASE OF MOUNT TO BE PARALLEL TO STRINGER. MOUNTS SHOWN AT CENTER OF ADJUSTMENT.
- (3) MINIMUM ANGLE OF EXHAUST DROP 4° (7/8 in./ft.) WITH BOAT IN WATER AT REST.
- (4) DIMENSIONS APPLY TO POINT OF INTERSECTION OF OUTPUT SHAFT CENTERLINE AND OUTPUT FLANGE FACE.

DIMENSIONS	12°	15°	PROP SHAFT ANGLE
A STANDARD	26-5/16	25-7/16	15°
A3 (3" RISER)	26	25-1/16	25-7/16
A6 (6" RISER)	29	28-1/16	25-1/16
B	11-15/16	12-13/16	28-1/16
C	21-1/16	21-3/16	12-13/16
D	8-15/16	9-1/4	21-3/16
E	2-3/16	1-13/16	9-1/4
F	8	7-7/8	1-13/16
G	3-7/16	3	8
H	17-5/16	15-1/2	3-7/16
J	24-3/8	22-3/4	17-5/16
K	33-9/16	34-1/2	24-3/8
L	5-5/16	4-1/4	33-9/16
M	9-15/16	10-7/16	5-5/16
N	38-5/8	39-5/16	9-15/16
P	5-1/8	5-9/16	38-5/8
R	1-3/16	1-3/16	5-1/8
S	1-3/8	1-3/8	1-3/16

ENGLISH
IN.

DIMENSIONS	12°	15°	PROP SHAFT ANGLE
A STANDARD	668	646	15°
A3 (3" RISER)	661	637	668
A6 (6" RISER)	737	713	661
B	303	310	737
C	535	538	303
D	227	235	535
E	55	47	227
F	204	201	55
G	88	75	204
H	439	394	88
J	619	557	439
K	853	877	619
L	135	107	853
M	252	266	135
N	981	999	252
P	131	142	981
R	30	31	131
S	35	34	30

METRIC
MM.