



DIMENSIONS	PROPSHAFT ANGLE		
	10°	12°	15°
A	618	651	699
A3	626	651	699
A6	702	719	743
B	360	363	368
C	640	640	637
D	154	146	135
E	113	121	133
F	242	242	243
G	134	140	147
H	385	384	381
K	980	964	937
L	(-) <sup>3</sup>	19	52
M	136	129	118
N	40	51	67
P	214	203	185
R	287	291	295

METRIC  
MM.

DIMENSIONS	PROPSHAFT ANGLE		
	10°	12°	15°
A	24-5/16	25-5/8	27-1/2
A3	24-5/8	25-5/8	27-1/2
A6	27-5/8	28-5/16	29-1/4
B	14-1/8	14-5/16	14-1/2
C	25-3/16	25-3/16	25-1/16
D	6-1/16	5-3/4	5-5/16
E	4-7/16	4-3/4	5-1/4
F	9-9/16	9-9/16	9-9/16
G	5-5/16	5-1/2	5-13/16
H	15-3/16	15-1/8	15
K	38-9/16	37-15/16	36-7/8
L	(-) <sup>1</sup> /8	3/4	2-1/16
M	5-3/8	5-1/16	4-5/8
N	1-9/16	2	2-11/16
P	8-7/16	8	7-5/16
R	11-5/16	11-7/16	11-5/8

ENGLISH  
IN.

UNIT OF MEASURE in. (mm)	SCALE APPROX. 1" = 1' 25.4mm = 304mm
-----------------------------	--------------------------------------------

MIE 8.2L MPI WITH HURTH 800A  
DOWN ANGLE TRANSMISSION.

- (1) DIMENSIONS REQUIRE A MINIMUM 1/2 in. (13mm) CLEARANCE FOR MOTOR MOUNT DEFLECTION.
- (2) BASE OF MOUNT TO BE PARALLEL TO STRINGER. MOUNTS SHOWN AT CENTER OF ADJUSTMENT.
- (3) MINIMUM ANGLE OF EXHAUST DROP 6 ° (1-1/4 in./ft.) WITH BOAT IN WATER AT REST.
- (4) DIMENSIONS APPLY TO POINT OF INTERSECTION OF OUTPUT SHAFT CENTERLINE AND OUTPUT FLANGE FACE.