



DIMENSIONS	PROPSHAFT ANGLE		
	10°	12°	15°
A	621	650	691
A3	621	650	691
A6	661	675	695
B	315	318	322
C	632	633	633
D	133	132	125
G	65	69	76
H	271	267	260
K	870	854	828
L	38	16	(-)/18
N	119	126	136
P	225	213	194
R	227	229	232

METRIC  
MM.

DIMENSIONS	PROPSHAFT ANGLE		
	10°	12°	15°
A	24-7/16	25-9/16	27-3/16
A3	24-7/16	25-9/16	27-3/16
A6	26-1/16	26-9/16	27-3/8
B	12-7/16	12-9/16	12-11/16
C	24-7/8	24-15/16	24-15/16
D	5-1/4	5-3/16	4-15/16
G	2-9/16	2-3/4	3
H	10-11/16	10-1/2	10-1/4
K	34-1/4	33-5/8	32-9/16
L	1-1/2	5/8	(-)/11/16
N	4-11/16	4-15/16	5-5/16
P	8-7/8	8-3/8	7-5/8
R	8-15/16	9	9-1/8

ENGLISH  
IN.

UNIT OF MEASURE in. (mm)	SCALE APROX. 1" = 1' 25.4mm = 304mm
-----------------------------	---

MIE 350 MAG MPI WITH VELVET DRIVE 71C  
IN-LINE TRANSMISSION.

- (1) DIMENSIONS REQUIRE A MINIMUM 1/2 in. (13mm) CLEARANCE FOR MOTOR MOUNT DEFLECTION.
- (2) BASE OF MOUNT TO BE PARALLEL TO STRINGER. MOUNTS SHOWN AT CENTER OF ADJUSTMENT.
- (3) MINIMUM ANGLE OF EXHAUST DROP 6 °(1-1/4 in./ft.) WITH BOAT IN WATER AT REST.
- (4) DIMENSIONS APPLY TO POINT OF INTERSECTION OF OUTPUT SHAFT CENTERLINE AND OUTPUT FLANGE FACE.