



DIMENSIONS	10-	12-	15-
A STANDARD (1)	571	595	622
A3 (3" RISERS) (1)	622	640	662
A6 (6" RISERS) (1)	697	697	706
B	348	353	355
C	550	550	549
D (3)	182	174	163
E (3)	142	148	157
F (1)	204	203	205
G	209	209	270
G'	209	301	303
H	147	138	124
J (2)	-22	-3	26
K (3)	371	381	346
L (3)	133	141	152
M	268	269	269
N	167	171	175

METRIC
MM.

DIMENSIONS	10-	12-	15-
A STANDARD (1)	22-1/2	23-7/16	24-7/8
A3 (3" RISERS) (1)	24-1/2	25-3/16	26-1/8
A6 (6" RISERS) (1)	27-1/16	27-7/16	27-7/8
B	13-1/16	13-7/8	14
C	21-5/8	21-5/8	21-5/8
D (3)	7-3/16	6-7/8	6-3/8
E (3)	5-5/8	5-13/16	6-3/16
F (1)	9-3/16	9-1/4	9-1/4
G	10-9/16	10-5/8	10-5/8
G'	11-13/16	11-7/8	11-15/16
H	5-13/16	5-7/16	4-7/8
J (2)	1-7/8	1-11/16	1
K (3)	14-5/8	14-1/4	13-5/8
L (3)	5-1/4	5-9/16	6
M	10-9/16	10-9/16	10-9/16
N	6-9/16	6-11/16	6-7/8

ENGLISH
IN.

MIE 7.4L MPI BLUEWATER WITH (VELVET DRIVE 5000A) DOWN-ANGLE TRANSMISSION

- NOTES:
 (1) Dimensions Require a Minimum 1/2 in. (13mm) Clearance for Motor Mount Deflection.
 (2) Base of Mount to be Parallel to Spring Mounts Shown at Center Section of Output Shaft Centerline and Output Flange Face.
 (3) Dimensions Apply to Point of Inter-section of Output Shaft Centerline and Output Flange Face.
 (4) Minimum Angle of Exhaust Drop 6 (1-1/4 in./ft.) With Boat in Water at Rest.