



MIE 8.2L MPI BLUEWATER WITH  
VELVET DRIVE 72C IN-LINE TRANSMISSION

- NOTES:  
 (1) Dimensions Require a Minimum 1/2 in. (13mm) Clearance for Motor Mount Deflection.  
 (2) Base of Mount to be Parallel to Stringer, Mounts Shown at Center of Adjustment.  
 (3) Adjustment Apply to Point of Intersection of Output Shaft Centerline and Output Flange Face.  
 (4) Minimum Angle of Exhaust Drop 6 (1-1/4 in./ft.) With Boat in Water at Rest.

DIMENSIONS	10-	12-	15--
A STANDARD (1)	25-1/2	26-7/8	28-1/8
A3 (2' RISERS) (1)	26	26-1/8	26-1/8
A6 (6' RISERS) (1)	26-7/8	27-1/8	27-1/2
B	14-5/16	14-7/16	14-9/16
C	24-11/16	24-11/16	24-9/16
D (3)	6-3/16	5-15/16	5-5/8
E (3)	3-1/2	3-1/16	4
F (1)	10-1/4	9-3/4	9
G	8-1/8	8-1/4	8-3/8
H (2)	(-)	5/8	1-7/8
J	11-1/2	11-1/8	10-3/8
K	3-13/16	3-13/16	3-13/16
L	3-7/8	3-7/8	3-7/8
M	10-11/16	10-7/8	11-1/8
N	3-13/16	3-9/16	3-3/16

ENGLISH  
IN.

DIMENSIONS	10-	12-	15--
A STANDARD (1)	648	682	681
A3 (2' RISERS) (1)	661	662	713
A6 (6' RISERS) (1)	683	689	689
B	345	367	370
C	627	626	624
D (3)	157	152	143
E (3)	88	94	101
F (1)	260	247	228
G	206	209	212
H (2)	(-)	16	48
J	292	281	263
K	97	97	97
L	98	98	98
M	272	276	282
N	97	91	81

METRIC  
MM.