



MIE 8.2L MPI BLUEWATER WITH VELVET DRIVE 5000A) DOWN-ANGLE TRANSMISSION

- NOTES:
 (1) Dimensions Require a Minimum 1/2 in. (13mm) Clearance for Motor Mount Deflection.
 (2) Base of Mount to be Parallel to Stringer Mounts Shown at Center of Adjustment.
 (3) Dimensions Apply to Point of Intersection of Output Flange Face and Output Flange Face.
 (4) Motor Mounts must Drop 6 (1.25 in./ft.) With Boat in Water at Rest.

DIMENSIONS	10~	12~	15~
A STANDARD (1)	21-1/8	21-7/8	21-15/16
A3 (3° RISERS) (1)	24-7/16	24-13/16	25-13/16
A4 (6° RISERS) (1)	27	27-1/2	28-1/4
B	13-11/16	13-7/8	14
C	21-5/8	21-5/8	21-5/8
D (3)	7-3/16	6-7/8	6-3/8
E (3)	5-5/8	5-13/16	6-3/16
F (1)	9-3/16	9-1/4	9-1/4
G	10-9/16	10-5/8	10-5/8
H	11-13/16	11-7/8	11-13/16
J	5-13/16	5-7/16	4-7/8
K	13	12-7/8	12-11/16
L	14-5/8	14-1/4	13-5/8
M	5-1/4	5-9/16	6
N	6-9/16	6-11/16	6-7/8
P	25-13/16	24-3/4	26-1/8
R	1-15/16	1-5/8	1-1/8

DIMENSIONS	10~	12~	15~
A STANDARD (1)	536	545	559
A3 (3° RISERS) (1)	620	630	656
A4 (6° RISERS) (1)	688	699	718
B	348	353	365
C	550	550	549
D (3)	182	174	163
E (3)	142	148	157
F (1)	234	235	235
G	269	269	270
H	299	301	303
J	147	138	124
K	273	269	261
L	330	327	323
M	371	361	346
N	133	141	152
P	664	659	664
R	48	41	28

ENGLISH
IN.

METRIC
MM.