



UNIT OF MEASURE in. (mm)	SCALE APPROX. 1" = 1" 25.4mm = 304mm
-----------------------------	--

MIE 8.1L MPI WITH HURTH 630V
V-DRIVE TRANSMISSION.

- (1) DIMENSIONS REQUIRE A MINIMUM 1/2 in. (13mm) CLEARANCE FOR MOTOR MOUNT DEFLECTION.
- (2) BASE OF MOUNT TO BE PARALLEL TO STRINGER. MOUNTS SHOWN AT CENTER OF ADJUSTMENT.
- (3) MINIMUM ANGLE OF EXHAUST DROP 4 ° (7/8 in./ft.) WITH BOAT IN WATER AT REST.
- (4) DIMENSIONS APPLY TO POINT OF INTERSECTION OF OUTPUT SHAFT CENTERLINE AND OUTPUT FLANGE FACE.

DIMENSIONS	PROPSHAFT ANGLE	
	12°	15°
A3 (3" RISER)	26-1/2	25-3/16
A6 (6" RISER)	29-1/2	28-1/8
B	14-11/16	15-1/8
C	27-1/4	27-3/8
D	5-5/8	6
E	5-11/16	5-1/2
F	9-3/16	9-1/4
G	5	4-11/16
H	19-11/16	18-1/8
J	19-5/8	17-9/16
K	26-1/16	24
L	4-9/16	3-1/8
M	8-1/16	8-5/16
N	30-1/16	30-15/16
P	5-13/16	7-3/8
R	13-9/16	3-7/16
S	15-3/4	15-1/4
T	7-7/8	8-1/2
U	13/16	7/16

ENGLISH
IN.

DIMENSIONS	PROPSHAFT ANGLE	
	12°	15°
A3 (3" RISER)	673	639
A6 (6" RISER)	750	715
B	372	384
C	692	695
D	143	152
E	145	139
F	233	235
G	126	119
H	500	460
J	498	445
K	661	610
L	116	80
M	206	211
N	763	786
P	147	188
R	345	342
S	399	387
T	200	217
U	21	11

METRIC
MM.