



DIMENSIONS	PROPSHAFT ANGLE	
	12°	15°
A	661	638
A3	661	638
A6	737	713
B	303	300
C	535	536
D	227	235
E	55	47
F	204	201
G	88	75
H	439	394
J	619	557
K	853	877
L	3	(-)25
M	252	266
N	981	999
P	131	142
R	30	31
S	35	34

METRIC
MM.

DIMENSIONS	PROPSHAFT ANGLE	
	12°	15°
A	26	25-1/8
A3	26	25-1/8
A6	29	28-1/16
B	11-15/16	11-13/16
C	21-1/16	21-1/8
D	8-15/16	9-1/4
E	2-3/16	1-13/16
F	8	7-7/8
G	3-7/16	3
H	17-5/16	15-1/2
J	24-3/8	22-3/4
K	33-9/16	34-1/2
L	1/8	(-)1
M	9-15/16	10-7/16
N	38-5/8	39-5/16
P	5-1/8	5-9/16
R	1-3/16	1-3/16
S	1-3/8	1-3/8

ENGLISH
IN.

UNIT OF MEASURE in. (mm)	SCALE APROX. 1" = 1' 25.4mm = 304mm
-----------------------------	---

MIE 350 MAG MPI HORIZON WITH VELVET DRIVE 5000V
V-DRIVE TRANSMISSION.

- (1) DIMENSIONS REQUIRE A MINIMUM 1/2 in. (13mm) CLEARANCE FOR MOTOR MOUNT DEFLECTION.
- (2) BASE OF MOUNT TO BE PARALLEL TO STRINGER. MOUNTS SHOWN AT CENTER OF ADJUSTMENT.
- (3) MINIMUM ANGLE OF EXHAUST DROP 4 ° (7/8 in./ft.) WITH BOAT IN WATER AT REST.
- (4) DIMENSIONS APPLY TO POINT OF INTERSECTION OF OUTPUT SHAFT CENTERLINE AND OUTPUT FLANGE FACE.