



MIE 7.4L MPI BLUEWATER WITH VELVET DRIVE 72C IN-LINE TRANSMISSION

- NOTES:
 (1) Dimensions Require a Minimum 1/2 in. (13mm) Clearance for Motor Mount Deflection.
 (2) Base of Mount to be Parallel to Output Flange Face.
 (3) Dimensions Apply to Point of Intersection of Output Shaft Centerline and Output Flange Face.
 (4) Minimum Angle of Exhaust Drop 6 Degrees (1.05 rad) With Boat in Water at Rest.

DIMENSIONS	10-	12-	15-
A STANDARD (1)	23-3/8	23-15/16	24-3/4
A3 (3) RISERS (1)	24-11/16	26-1/16	26-15/16
A6 (3) RISERS (1)	26-3/16	27-1/8	28
B	14-5/16	14-7/16	14-9/16
C	24-11/16	24-11/16	24-9/16
D (3)	6-3/16	5-15/16	5-5/8
E (3)	3-1/2	3-11/16	4
F (1)	10-1/4	9-3/4	9
G	8-1/8	8-1/4	8-3/8
H (2)	(-) 1/4	5/8	1-7/8
J	11-1/2	11-1/16	10-3/8
K	4-3/16	3-13/16	3-1/4
L	3-7/8	3-7/8	3-7/8
M	26	26-7/8	26-11/16

ENGLISH
IN.

DIMENSIONS	10-	12-	15-
A STANDARD (1)	594	608	609
A3 (3) RISERS (1)	627	663	684
A6 (3) RISERS (1)	675	690	711
B	345	367	370
C	627	626	624
D (3)	157	152	143
E (3)	88	94	101
F (1)	260	247	228
G	206	209	212
H (2)	(-) 6	16	48
J	292	281	263
K	106	97	83
L	98	96	96
M	661	662	713

METRIC
MM.