



MIE 8.2L MPI BLUEWATER WITH VELVET DRIVE 5000V V-DRIVE TRANSMISSION

- NOTES:
 (1) Dimensions Require a Minimum 1/2 in. (13mm) Clearance for Motor Mount Deflection.
 (2) Base of Mount to be Parallel to Stringer. Mounts Shown at Center section of Output Shaft Centerline and Output Flange Face.
 (4) Minimum Angle of Exhaust Drop 4 (7/8 in./ft.) With Boat in Water at Rest.

| DIMENSIONS | PROPSHAFT ANGLE | |
|---------------------------|-----------------|----------|
| | 12° | 15° |
| A STANDARD | 21-7/8 | 21-15/16 |
| A ₁ (3° RISER) | 19-3/4 | 20-7/16 |
| A ₂ (6° RISER) | 25-3/4 | 26-7/16 |
| B | 14-1/8 | 13-1/2 |
| C | 22-1/4 | 22-1/4 |
| D | 7-13/16 | 7-9/8 |
| E | 2-3/16 | 2-7/16 |
| F | 12-3/16 | 12-13/16 |
| G | 7-7/8 | 8-5/8 |
| H | 5-1/2 | 4-11/16 |
| J | 12-1/16 | 11-15/16 |
| K | 10-1/16 | 10-1/4 |
| L | 13-1/16 | 12-13/16 |
| M | 21-13/16 | 23-1/4 |
| N | 5-1/4 | 5-1/4 |
| P | 10-1/16 | 9-7/8 |

| DIMENSIONS | PROPSHAFT ANGLE | |
|------------------------------|-----------------|-----|
| | 12° | 15° |
| A STANDARD | 556 | 598 |
| A ₁ (76mm RISER) | 501 | 620 |
| A ₂ (152mm RISER) | 653 | 672 |
| B | 359 | 342 |
| C | 565 | 565 |
| D | 189 | 187 |
| E | 55 | 63 |
| F | 316 | 325 |
| G | 200 | 218 |
| H | 139 | 118 |
| J | 307 | 303 |
| K | 484 | 464 |
| L | 395 | 401 |
| M | 553 | 591 |
| N | 57 | 57 |
| P | 256 | 251 |

ENGLISH IN.

METRIC MM.