

EXHAUST OUTLET DIA. 4"
(102) X 2"(51) LONG
(2)(3)

REMOTE OIL
FILTER

THROTTLE CABLE
CONNECTION

(-)BATTERY
TERMINAL
CONNECTION

ELECTRICAL
HARNESS
RECEPTACLE

CRANKSHAFT
C.L.

CHECK VALVE

$9\frac{9}{16}$ [243]

SINGLE POINT
WATER DRAIN

4 [102]
(3/8 [10] NOM. DIA. BOLT HOLES)

$21\frac{1}{8}$ [555]
WITH 3" RISER
(1)(2)

$18\frac{1}{8}$ [479]

$\frac{5}{8}$ [93]

MOUNTING
BRACKETS ADJUST
1/2 IN.[13]
UP OR DOWN

864695 SHEET 2 OF 3
4.3L MPI JACKSHAFT

UNIT OF MEASURE in. [mm]	SCALE 1" = 1' 25.4mm = 304mm
-----------------------------	------------------------------------

NOTES:

- (1) DIMENSIONS REQUIRE A MINIMUM 1/2 in. (13mm) CLEARANCE FOR MOTOR MOUNT DEFLECTION.
- (2) SELECT THE APPROPRIATE EXHAUST RISE-HEIGHT TO MAINTAIN A MINIMUM OF 13 in. (330mm) BETWEEN THE TOP OF THE EXHAUST ELBOW AND THE WATERLINE OF THE BOAT AT MAXIMUM RATED LOAD.
- (3) EXHAUST OUTLETS MUST BE ABOVE WATERLINE OF BOAT AT MAXIMUM RATED LOAD.