



DIMENSIONS	PROP SHAFT ANGLE
A, STANDARD	12-15
A <sub>1</sub> (6" RISER)	24-9/16
A <sub>1</sub> (7" RISER)	25-1/4
A <sub>1</sub> (8" RISER)	26-1/2
A <sub>1</sub> (9" RISER)	25-9/16
B	28
C	29-3/8
D	14-1/8
E	11-11/16
F	27-3/8
G	6
H	6-1/4
J	6-1/8
K	5-1/2
L	9-3/16
M	9-3/16
N	5
P	4-11/16

DIMENSIONS	PROP SHAFT ANGLE
A, STANDARD	1.5-
A <sub>1</sub> (76mm RISER)	624
A <sub>1</sub> (152mm RISER)	673
B	712
C	373
D	369
E	679
F	695
G	159
H	152
J	156
K	139
L	233
M	234
N	128
P	119

- NOTES:
- (1) Dimensions Require a Minimum 3/4 in. (19mm) Clearance for Motor Mount Deflection.
  - (2) Base of Mount to be Parallel to Stringer; Mounts Shown at Center of Adjustment.
  - (3) Dimensions Apply to Point of Intersection of Output Shaft Centerline and Output Flange Face.
  - (4) Minimum Angle of Exhaust Drop 4 (7/8 in./ft.) With Boat in Water at Rest.

ENGLISH  
IN.

METRIC  
MM.