



DIMENSIONS	PROPSHAFT ANGLE		
	10°	12°	15°
A STANDARD	610	630	660
A3 (3" RISER)	610	630	660
A6 (6" RISER)	678	693	715
B	307	309	313
C	624	625	625
D	147	140	130
E	64	72	83
F	190	190	193
G	112	117	124
H	361	358	352
J	576	607	652
K	926	911	887
L	50	28	(-)5
M	143	136	126
N	88	99	113
P	195	184	167
R	292	295	299

METRIC  
MM.

DIMENSIONS	PROPSHAFT ANGLE		
	10°	12°	15°
A STANDARD	24	24-13/16	26
A3 (3" RISER)	24	24-13/16	26
A6 (6" RISER)	26-11/16	27-5/16	28-3/16
B	12-1/16	12-3/16	12-5/16
C	24-9/16	24-5/8	24-5/8
D	5-3/4	5-1/2	5-1/8
E	2-9/16	2-13/16	3-1/4
F	7-1/2	7-1/2	7-9/16
G	4-7/16	4-5/8	4-7/8
H	14-1/4	14-1/16	13-7/8
J	22-11/16	23-7/8	25-11/16
K	36-7/16	35-7/8	34-15/16
L	1-5/16	1-1/8	(-)/3/16
M	5-5/8	5-3/8	4-15/16
N	3-1/2	3-7/8	4-7/16
P	7-11/16	7-1/4	6-9/16
R	11-1/2	11-5/8	11-3/4

ENGLISH  
IN.

UNIT OF MEASURE in. (mm)	SCALE APROX. 1" = 1" 25.4mm = 304mm
-----------------------------	---

MIE 350 MAG MPI WITH HURTH 630A  
DOWN ANGLE TRANSMISSION.

- (1) DIMENSIONS REQUIRE A MINIMUM 1/2 in. (13mm) CLEARANCE FOR MOTOR MOUNT DEFLECTION.
- (2) BASE OF MOUNT TO BE PARALLEL TO STRINGER. MOUNTS SHOWN AT CENTER OF ADJUSTMENT.
- (3) MINIMUM ANGLE OF EXHAUST DROP 6 °(1-1/4 in./ft.) WITH BOAT IN WATER AT REST.
- (4) DIMENSIONS APPLY TO POINT OF INTERSECTION OF OUTPUT SHAFT CENTERLINE AND OUTPUT FLANGE FACE.