



- NOTES:
- (1) Dimensions Require a Minimum 3/4 in. (19mm) Clearance for Motor Mount Deflection.
  - (2) Base of Mount to be Parallel to Stringer. Mounts Shown at Center of Adjustment.
  - (3) Dimensions Apply to Point of Intersection of Output Shaft Centerline and Output Flange Face.
  - (4) Minimum Angle of Exhaust Drop 4 (7/8 in./ft.) With Boat in Water at Rest.

DIMENSIONS	12~	15~
A STANDARD	25-1/2	24-13/16
A <sub>1</sub> (3" RISER)	26-1/2	25-5/8
A <sub>2</sub> (6" RISER)	29-3/8	28
B	14-1/8	14-11/16
C	27-1/4	27-3/8
D	5-5/8	6
E	5-9/16	5-1/2
F	9-3/16	9 1/4
G	5	4-11/16
H	8-1/16	8-5/16
J	15-3/4	15-1/4
K	19-1/16	19-11/16
L	17-5/8	15-3/16
M	25-7/16	23-5/16
N	1-7/16	0
P	6-7/16	7-3/16

ENGLISH  
IN.

DIMENSIONS	12~	15~
A STANDARD	648	630
A <sub>1</sub> (76mm RISER)	673	650
A <sub>2</sub> (152mm RISER)	746	712
B	359	373
C	692	696
D	144	152
E	141	139
F	233	235
G	126	119
H	206	211
J	399	387
K	484	500
L	448	386
M	646	592
N	36	0
P	163	183

METRIC  
MM.