



- NOTES:**
- (1) Dimensions Require a Minimum 3/4 in. (19mm) Clearance for Motor Mount Deflection.
 - (2) Base of Mount to be Parallel to Stringer. Mounts Shown at Center of Adjustment.
 - (3) Dimensions Apply to Point of Intersection of Output Shaft Centerline and Output Flange Face.
 - (4) Minimum Angle of Exhaust Drop 4 (7/8 in./ft.) With Boat in Water at Rest.

DIMENSIONS	PROP SHAFT ANGLE
A STANDARD	12- 15-
A ₁ (3" RISER)	25-1/2 24-13/16
A ₂ (6" RISER)	26-1/2 25-5/8
B	28-3/8 28
C	14-1/8 14-11/16
D	27-1/4 27-3/8
E	5-5/8 6
F	5-9/16 5-1/2
G	9-3/16 9 1/4
H	5 4-11/16
J	8-1/16 8-5/16
K	15-3/4 15-1/4
L	19-1/16 19-11/16
M	17-5/8 15-3/16
N	25-7/16 23-5/16
P	1-7/16 0
	6-7/16 7-3/16

ENGLISH
IN.

DIMENSIONS	PROP SHAFT ANGLE
A STANDARD	12- 15-
A ₁ (76mm RISER)	648 630
A ₂ (152mm RISER)	673 650
B	746 712
C	359 373
D	692 696
E	144 152
F	141 139
G	233 235
H	126 119
J	206 211
K	389 387
L	484 500
M	448 386
N	646 592
P	36 0
	163 183

METRIC
MM.