



| DIMENSIONS | PROPSHAFT ANGLE | | |
|------------|-----------------|-----|-------|
| | 10° | 12° | 15° |
| A | 621 | 650 | 691 |
| A3 | 621 | 650 | 691 |
| A6 | 661 | 675 | 695 |
| B | 315 | 318 | 322 |
| C | 632 | 633 | 633 |
| D | 133 | 132 | 125 |
| G | 65 | 69 | 76 |
| H | 271 | 267 | 260 |
| K | 870 | 854 | 828 |
| L | 38 | 16 | (-)18 |
| N | 119 | 126 | 136 |
| P | 225 | 213 | 194 |
| R | 227 | 229 | 232 |

METRIC
MM.

| DIMENSIONS | PROPSHAFT ANGLE | | |
|------------|-----------------|----------|----------|
| | 10° | 12° | 15° |
| A | 24-7/16 | 25-9/16 | 27-3/16 |
| A3 | 24-7/16 | 25-9/16 | 27-3/16 |
| A6 | 26-1/16 | 26-9/16 | 27-3/8 |
| B | 12-7/16 | 12-9/16 | 12-11/16 |
| C | 24-7/8 | 24-15/16 | 24-15/16 |
| D | 5-1/4 | 5-3/16 | 4-15/16 |
| G | 2-9/16 | 2-3/4 | 3 |
| H | 10-11/16 | 10-1/2 | 10-1/4 |
| K | 34-1/4 | 33-5/8 | 32-9/16 |
| L | 1-1/2 | 5/8 | (-)11/16 |
| N | 4-11/16 | 4-15/16 | 5-5/16 |
| P | 8-7/8 | 8-3/8 | 7-5/8 |
| R | 8-15/16 | 9 | 9-1/8 |

ENGLISH
IN.

| | |
|-----------------------------|--|
| UNIT OF MEASURE in. (mm) | SCALE APPROX. 1" = 1' 25.4mm = 304mm |
|-----------------------------|--|

MIE 5.7L WITH VELVET DRIVE 71C
IN-LINE TRANSMISSION.

- (1) DIMENSIONS REQUIRE A MINIMUM 1/2 in. (13mm) CLEARANCE FOR MOTOR MOUNT DEFLECTION.
- (2) BASE OF MOUNT TO BE PARALLEL TO STRINGER. MOUNTS SHOWN AT CENTER OF ADJUSTMENT.
- (3) MINIMUM ANGLE OF EXHAUST DROP 6 ° (1-1/4 in./ft.) WITH BOAT IN WATER AT REST.
- (4) DIMENSIONS APPLY TO POINT OF INTERSECTION OF OUTPUT SHAFT CENTERLINE AND OUTPUT FLANGE FACE.