



DIMENSIONS	PROPSHAFT ANGLE	
	12°	15°
A STANDARD	624	603
A3 (3" RISER)	641	609
A6 (6" RISER)	718	685
B	303	300
C	692	692
D	143	152
E	141	140
F	233	235
G	126	119
H	420	360
J	599	550
K	1009	1032
L	17	53
M	206	211
N	1137	1155
P	150	169
R	345	342
S	399	387

METRIC
MM.

DIMENSIONS	PROPSHAFT ANGLE	
	12°	15°
A STANDARD	24-9/16	23-3/4
A3 (3" RISER)	25-1/4	24
A6 (6" RISER)	28-1/4	25-15/16
B	11-15/16	11-13/16
C	27-1/4	27-1/4
D	5-5/8	6
E	5-9/16	5-1/2
F	9-3/16	9-1/4
G	5	4-11/16
H	16-1/2	14-3/16
J	23-9/16	21-5/8
K	39-3/4	40-5/8
L	11/16	2-1/16
M	8-1/16	8-5/16
N	44-3/4	45-7/16
P	5-15/16	6-11/16
R	13-9/16	13-7/16
S	15-3/4	15-1/4

ENGLISH
IN.

UNIT OF MEASURE in. (mm)	SCALE APROX. 1" = 1' 25.4mm = 304mm
-----------------------------	---

MIE 5.7L WITH HURTH 630V
V-DRIVE TRANSMISSION.

- (1) DIMENSIONS REQUIRE A MINIMUM 1/2 in. (13mm) CLEARANCE FOR MOTOR MOUNT DEFLECTION.
- (2) BASE OF MOUNT TO BE PARALLEL TO STRINGER. MOUNTS SHOWN AT CENTER OF ADJUSTMENT.
- (3) MINIMUM ANGLE OF EXHAUST DROP 4 ° (7/8 in./ft.) WITH BOAT IN WATER AT REST.
- (4) DIMENSIONS APPLY TO POINT OF INTERSECTION OF OUTPUT SHAFT CENTERLINE AND OUTPUT FLANGE FACE.